



1B256 – 60° Dichtkegel mit BSP-Überwurfmutter 90° Bogen



WERKSTOFF Stahl, verzinkt, transparent Cr(VI)-frei passiviert.
Weitere Werkstoffe auf Anfrage.

Artikelnummer #	DN size mm Zoll				Anschlussart		A mm	B mm	E mm	J mm	Max. WP MPa
					Gewindegröße 	Rohr AD Zoll 					
1B256-4-3	5	-03	4,8	3/16	G 1/4	1/4	46	28	28	19	63,0
1B256-4-4	6	-04	6,4	1/4	G 1/4	1/4	53	29	28	19	63,0
1B256-6-5	8	-05	7,9	5/16	G 3/8	3/8	55	30	30	22	55,0
1B256-6-6	10	-06	9,5	3/8	G 3/8	3/8	58	33	33	22	55,0
1B256-8-8	12	-08	12,7	1/2	G 1/2	1/2	68	40	40	27	43,0
1B256-10-8	12	-08	12,7	1/2	G 5/8	5/8	68	41	38	30	37,5
1B256-12-12	20	-12	19,0	3/4	G 3/4	3/4	87	53	51	32	35,0
1B256-16-16	25	-16	25,4	1	G 1	1	115	67	63	41	28,0

1B456 – 60° Dichtkegel mit BSP-Überwurfmutter 90° Bogen – Kompakt



WERKSTOFF Stahl, verzinkt, transparent Cr(VI)-frei passiviert.
Weitere Werkstoffe auf Anfrage.

Artikelnummer #	DN size mm Zoll	Gewindegröße	A mm	B mm	J mm	Max. WP MPa
1B456-4-4	6 -04 6,4 1/4	G 1/4	47	23	19	63,0
1B456-6-6	10 -06 9,5 3/8	G 3/8	52	27	22	55,0
1B456-8-8	12 -08 12,7 1/2	G 1/2	58	31	27	43,0